

# **LKT4101**

## **8-BIT ENCRYPTION MICROCONTROLLER**

### **DATA SHEET**

**Revision 0**

The information in this publication has been carefully checked and is believed to be entirely accurate at the time of publication. Lingke Xin'an Technology(Beijing) Co., Ltd. assumes no responsibility, however, for possible errors or omissions, or for any consequences resulting from the use of the information contained herein.

Lingke Xin'an Technology(Beijing) Co., Ltd. reserves the right to make changes in its products or product specifications with the intent to improve function or design at any time and without notice and is not required to update this documentation to reflect such changes.

This publication does not convey to a purchaser of semiconductor devices described herein any license under the patent rights of Lingke Xin'an Technology(Beijing) Co., Ltd. or others.

Lingke Xin'an Technology(Beijing) Co., Ltd. makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does Lingke Xin'an Technology(Beijing) Co., Ltd. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation any consequential or incidental damages.

"Typical" parameters can and do vary in different applications. All operating parameters, including "Typicals" must be validated for each customer application by the customer's technical experts.

Lingke Xin'an Technology(Beijing) Co., Ltd. products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, for other applications intended to support or sustain life, or for any other application in which the failure of the Lingke Xin'an Technology(Beijing) Co., Ltd. product could create a situation where personal injury or death may occur.

Should the Buyer purchase or use a Lingke Xin'an Technology(Beijing) Co., Ltd. product for any such unintended or unauthorized application, the Buyer shall indemnify and hold Lingke Xin'an Technology(Beijing) Co., Ltd. and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, expenses, and reasonable attorney fees arising out of, either directly or indirectly, any claim of personal injury or death that may be associated with such unintended or unauthorized use, even if such claim alleges that Lingke Xin'an Technology(Beijing) Co., Ltd. was negligent regarding the design or manufacture of said product.

## **LKT4101**

### **8-BIT ENCRYPTION MICROCONTROLLER**

#### **Data Sheet, Revision 0**

#### **Publication Number: LKT4101-11-2011**

© 2011 Lingke Xin'an Technology(Beijing) Co., Ltd.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electric or mechanical, by photocopying, recording, or otherwise, without the prior written consent of Lingke Xin'an Technology(Beijing) Co., Ltd.

Home Page: <http://www.lingkes.com.cn>

E-mail : [technic@lingkes.com](mailto:technic@lingkes.com)

## FEATURES

### CPU

- 80X51 industry standard
- Accelerated architecture with 16 bit CPU performance level
- Up to 40 MHz internal CPU clock

### Memory Allocation

- 52K-Bytes for user data area
- 2048 bytes RAM (256B Local RAM + 1792B XRAM)

### Flash Operations

- Min. 100,000 erase/write cycles
- Min. 10 years data retention

### Data Security

- Hardware Random Number Generator FIPS140-2
- Unique chip identification number
- Notification of tampering
- IC operates under regulated voltage and internal clock
- Combined HW/SW DPA/SPA resistance mechanisms
- Under / Over voltage sensors (Vcc)
- Dynamic RAM data encryption
- Security optimized layout

### MPU (Memory Protection Unit)

- Individual protection attributes up to 8 separate regions

### Serial I/O Interface (UART)

- Asynchronous half-duplex serial interface which conforms to ISO 7816-3
- One hardware UART supporting T=0 and T=1

### Parity/CRC calculator

- Parity calculator for 8/16/32 bit
- CRC-16/32 calculator

### Clock Controller

- External Clock
- Internal RC clock

### Reset

- Power-on reset and external reset
- Power-on reset flag

### Operating Characteristics

- Single power supply: 3.0V- 5.0V  $\pm$  10%
- Operating frequency: 1 to 5MHz (External clock @class A/B.)
- Operating temperature: - 25 °C -+ 85 °C
- > 4 kV ESD Protection HBM


### Operating Current

- Idle and Stop mode selectable modes
- NVM update operation with CPU in idle mode
- IO Transmission and Reception with CPU in idle mode
- Max Idle current / Clock stopped: 100 uA

## PIN ASSIGNMENTS

**Table 1. LKT4101 Pin Descriptions**

Pin Number	Pin Name	Function Description	Pin Type
C1	Vss	Ground	---
C2	NC	No connection	---
C3	I/O	Serial data input and output pin	Input/output
C4	NC	No connection	---
C5	NC	No connection	---
C6	CLK	External clock input	input
C7	RST	System reset input	input
C8	Vcc	Power input	----



**Technical Data**
**Absolute Maximum Ratings**

Parameter	Symbol	Limit Values			Unit
		min	typical	max	
Supply Operating Volt	$V_{cc}$	-0.3		6	V
Voltage at remaining pin	$V_{pin}$	$V_{ss} - 0.3$		$V_{cc} + 0.3$	V
Power dissipation	$P_{tot}$			+60	mW
Storage temperature	$I_{ocl}$	-40		+125	°C

**DC Characteristics**

Parameter	Symbol	Limit Values			Unit
		min	typical	max	
Operating temperature	$T_A$	-25		+85	°C
Supply Voltage Class A,B	$V_{cc}$	2.7	3 / 5	5.5	V
Supply Current Class B	$I_{cc}$			6 (Note 1)	mA
Supply Current idle	$I_{ocl}$			200 (Note 2)	μA
Supply Current stopped	$I_{ccs}$			100 (Note 3)	μA

Note 1: The supply current refers to clock frequency of 5 Mhz

Note 2: The supply current at 3.3V and a clock frequency of 1 Mhz, at +25 °C

Note 3: The supply current at 3.3V and +25 °C

**IO pin:**

Parameter	Symbol	Conditions	min	max	Unit
H input voltage	$V_{IH}$	$I_{IHmax} = \pm 20 \mu A$	$0.7 * V_{cc}$	$V_{cc}$	V
L input voltage	$V_{IL}$	$I_{ILmax} = \pm 20 \mu A$	-0.3	0.8	V
H output voltage (Note 1)	$V_{OH}$	$I_{OHmax} = +20 \mu A$	$0.7 * V_{cc}$	$V_{cc}$	V
L output voltage	$V_{OL}$	$I_{OLmax} = -1 mA$	0	0.4	V
Rise Fall Time	$t_r, t_f$	$C_{IN} = C_{OUT} = 30 pF$		1	μS

NOTE 1: Assumes 20KΩ Pull up resistor on interface device

**Clock (CLK)**

Parameter	Symbol	Condition	Min	Max	Unit
H output voltage	$V_{OH}$	$I_{OHmax} = +20 \mu A$	$V_{cc} - 0.7$	$V_{cc}$	V
L output voltage	$V_{OL}$	$I_{OLmax} = -20 \mu A$	0	0.5	V
Rise Fall Time	$t_r, t_f$	$C_{IN} = C_{OUT} = 30 pF$		9% CLK period	

**Reset(RST)**

Parameter	Symbol	Condition	Min	Max	Unit
H output voltage	$V_{OH}$	$I_{OHmax} = +20 \mu A$	$V_{cc} - 0.7$	$V_{cc}$	V
L output voltage	$V_{OL}$	$I_{OLmax} = -20 \mu A$	0	0.6	V
Rise Fall Time	$t_r, t_f$	$C_{IN} = C_{OUT} = 30 pF$		400	μs